R			TRAN	A PAI	
. Seren at the	3,132-11,264-13	為於其他的學術			



CONTENTS-

1. Features 3
2. Name of Parts 4
3. Keys and Switches 5
4. Indicators 8
5. Preparations 9
6. Calculations 10
I. Basic Calculations 10
1. Addition 10
2. Subtraction 10
3. Multiplication 10
4. Successive Multiplication
5. Division 12
6. Successive Division
II. Advanced Calculations
1. Multiplication with a Constant 14
2. Division by a Constant 14
3. Mixed Calculation 15
4. Power Calculation 15
5. Addition and Subtraction of Products with Sub- Total and Grand Total
6. Product of Sum and Difference

	7. Addition and Subtraction of Quotient with Sub- Total and Grand Total
	8. Quotient of Sum and Difference
	9. Reciprocal of Calculation
III.	Practical Calculations 20
	1. Percentage Calculation 20
	2. Increase/Decrease Rate Calculation
	3. Invoice Calculation
	4. Depreciation Calculation
	5. Proportional Division
	6. Probability Calculation 24
	7. Credit Loan Payment Calculation
	8. Simple Interest/Compound Interest Calculation 27
	9. High-Power Multinominal Calculation
B. B	attery Recharging
. Sı	pecifications

1. FEATURES

1. Specially designed LSIs

The LSIs, specially designed by Sanyo, insure unsurpassed reliability.

2. Decimal point

The floating input/fixed output system is used allowing the operator to pre-select the decimal position required in the answer, regardless of the number of decimals entered in the problem. Decimal position are 0, 2, 3, 4, and 6 places.

3. Independent memory

A directly addressable memory allows entry of number into the memory. The sigma key allows accumulation of results for Grand Total.

4. Automatic constant

The first number in multiplication and second number in division are automatically set up as a constant.

- 5. True credit balance with a floating minus sign
 Sign appears immediately to the left-most digit number.
- 6. Round-off/Drop-off switch

 By using the round-off switch, all numbers are immediately rounded off.
- 7. Sequential operation


Chain multiplication or division can be accomplished without the need to attain unnecessary intermediate results.

8. Touch operation

Convenient, fast touch operation can be accomplished due to symmetric keyboard design.

2. NAME OF PARTS

AC adaptor



- Clear all key
- 2. Clear memory key
- Clear key
- 4. Recall memory key
- 5. Memory minus key
- 6. Memory plus key
- 7. Multiplication key
- 8. Division key
- 9. Plus key
- 10. Minus key

- Equal key
- 12. Sigma switch
- 3. Numeric keys
- 14. Decimal point key
- 5. Round-off switch
- 16. Decimal point selector switch
- 7. Power switch
- 8. Battery alarm lamp
- Error (over-flow) lamp/Minus sign indicator

3

3. KEYS AND SWITCHES-



Clears entire machine except the memory.

Clear All Key




Clears memory.

Clear Memory Key




Recalls and displays figure stored in the memory.

Recall Memory Key




Use this switch to accumulate totals for Grand Total.

Sigma Switch



Figures are indexed by touching these keys and are then displayed on the indicator.

Numeric Keys




When this key is depressed, the figures displayed are added to the memory and stored in the memory.

Memory Plus Key




When this key is depressed, the figures displayed are subtracted from the memory and stored in the memory.

Memory Minus Key




Used for additions. When this key is depressed, the contents of the display are added to the results of the previous calculation and the sum is displayed on the indicator.

Plus Key



Minus Key

Used for subtractions. When this key is depressed, the contents of the display are subtracted from the result of the previous calculation and the difference is displayed on the indicator.




1

14


In multiplications, depress this key after registering the multiplicand. The calculator is then in the multiplication position.

Multiplication Key




In divisions, depress this key after registring the dividend. The calculator is then in division position.

Division Key




Pre-select the position of the decimal point with this switch.

Decimal Point Selector Switch




Depress this key to obtain final answers. Also clear the working register.

Equal Key




The last digit displayed on the indicator is result of counting fraction over 1/2 as one and disregarding those below 1/2.

Round-off Key



witch



Depress this key at the appropriate position when registering the figures with a decimal point.

Decimal Point Key



Clears only the last figures registered.

Clear Key

4. INDICATORS

1. Figure display

Full size fluorescent tubes. Each figure including the decimal is formed from 9 segments, and the display, controlled by logic circuits, is as shown below.

1234557890.

2. Minus sign

The only time the minus sign indicator lights when the result is a negative figure as shown below.

-/23

3. Error (over-flow) lamp

When a figure or the result of a calculation exceeds capacity of calculator, this lamp lights and further calculation is impossible. Depress the key to clear the display. The error lamp will light in the following instances:

- a. When a figure registered into the calculator exceeds 14 digits.
- b. In additions and subtractions, when the number of figure registered into the calculator plus the number of pre-selected decimal figures exceed the capacity of calculator.
- 4. Battery alarm lamp

This lamp shows the condition of the rechargeable Cadnica battery. For further details, refer to the section on Battery Recharging.

5. PREPARATIONS

Prepare for operation in the following order before starting calculations.

- 1. Turn on the power switch.
- 2. Confirm that when the [1] key and [1] key are depressed, only the first digit shows 0 and the other digits go off.
- Check if the error lamp lights, when registering a random figure of more than 15 digits.
 If there are no anomalies in the above check, try the following simple calculations.
- (1) Set the decimal point selector switch at 2

Operation		Display	
1 • 23 +	→ <u></u>	1, 23	
456 =	-	457. 23	

(2) Set the round-off switch and the decimal point selector switch at 4.

CA	→	0
5 ÷		5.
9 =	-	0. 5556

(3) Set the round-off switch and the decimal point selector switch at 3.

1 - 23 ×	→	1. 23
	→	1, 513

6. CALCULATIONS

I. BASIC CALCULATIONS

I. ADDITION


Ex.	12.3+45.67=57.97		
	(FT) [CA]		
	12 - 3 +	- -	12.
	^{2©} 45 · 67 +	-	57.

2. SUBTRACTION

Ex. 1	24.8-11.5=13.3		
	[EA]	→ <u></u>	0
	24 • 8 +	→ [24. 80
	11 [-] 5 [-]		13.30
Ex. 2	18.6+24.9-14.2+3.8=33.1		
	(6T) (CA)	→	0
	18 - 6 +	-	18. 60
	24 • 9 +		43. 50
	14 • 2 -	→ <u></u>	29.30
	3 [-] 8 [+]	-	33.10

3. MULTIPLICATION

Ex. 1	123×27=3321		
	(F) CA		
	123 ×	-+	12
	2 27 =	→	332




NOTE 1 With multiplication or successive multiplication, clearing is automatic and there is no need to depress the CA key for each calculations.

NOTE 2 The product must not exceed 14 digits.

NOTE 3 When using $[\Sigma]$ key switch, [-] key is used as a exclusive minus entry key.

5. DIVISION



6. SUCCESSIVE DIVISION


Ex.	$18.2 \div 3.5 \div 2.3 = 2.260869$		
6T 34 (18 • 2 ÷	- <u>[</u>	18. 2
4	3 → 5 →		5. 2000
2 †	2 [-] 3 [=]	-	2. 2609

NOTE 1. In division, both dividend and divisor can be registered up to 14 digits.

NOTE 2. With division and successive division, clearing is automatic and there is no need to depress the M key for each calculations.

II. ADVANCED CALCULATIONS


1. MULTIPLICATION WITH A CONSTANT



- NOTE 1. In multiplication and division with a-constant, register the constant as multiplicand or divisor.
- NOTE 2. In these calculations, it is not necessary to depress the key or ÷ key for each calculations.

 If they are depressed during a calculation, a wrong result will be obtained.

3. MIXED CALCULATION




 $a^{n} = z$ (a is positive)

To show this calculation with an equation, it is equivalent to $2 \times 2 \times 2 \times 2 \times 2 \times 32$. Therefore, in calculating a^{Π} , the \times key should be depressed (n-1) times. Especially, if $n = 2, 4, 8, \dots 2^{m}$, the \times key and the = key should be depressed m times after registering a.

Ex. 2 38=6561		
(ST)	→	0
3 ×		3.
2		9.
		9.
		81.
\boxtimes	→	81.
	→	6561.

5. ADDITION AND SUBTRACTION OF PRODUCTS WITH SUBTOTAL AND GRAND TOTAL.




NOTE The CA and CM key must first be depressed to clear the result of the previous calculation

6. PRODUCT OF SUM AND DIFFERENCE

Ex.	$(47.2+29.8)\times(19.2-12.6)=508.2$		
	(CA)	→ [0
	s CM	[0
	47 · 2 ·		47. 20
	29 - 8 11	- [29. 80
	19 • 2 +	→ [19. 20
	12 [6 [-	→ [6. 60
	(=)	[6. 60
	\times	→ [6. 60
	RM)	→ [77. 00
		→ [508. 20

7. ADDITION AND SUBTRACTION OF QUOTIENT WITH SUBTOTAL AND GRAND TOTAL.



8. QUOTIENT OF SUM AND DIFFERENCE

Ex. 1	$(28+46)\div(22+31)=1.396$		
	(FT) [CA]	- E	0
	CM)	→	0
	2 22 M T	-	22. 000
	31 🗮		31.000
	28 🛨		28. 000
	46 [+]	→ [74.000
	=	> [74.000
	(÷)		74. 000
	RM		53. 000
			1.396

9. RECIPROCAL CALCULATION

Ex.	$\frac{1}{(2+3)\times 4+5}=0.04$		
	(T) CA	-+	0
	S CM		0
	2 +	-• <u></u>	2. 00
	3 =	-	5. 00
	[X]	-	5. 00
	4 =	→ [20.00
	[+]		20.00
	5 =	-	25. 00
			25. 00
	1 <u>÷</u>		1:
	RM		25.00
		→ <u> </u>	0.04

III. PRACTICAL CALCULATIONS

Ex.	Sales brea	kdown in pe	ercentage.		
A	Dept.	\$ 123,	000		
В	Dept.	\$ 456,	000		
C	Dept.	\$ 789,	000		
		5/4	[EA]		0
		3 🗐	CM	→ [0
		2	123000 +		123000.000
		(OI)	456000 [+]	> [579000.000
			789000 [+]	→ [1368000.000
				→ [1368000.000
			M +		1368000.000
			123000 ÷		123000.
			RM		1368000.000
			=	→ [0.090
			456000 =		0. 333
			789000 =	[0. 577
INCR	EASE/DEC	REASE RA	TE CALCULATI	ON	


last month's sales

0		N3	6T 5/4 (
0	-	C#	; U
5024000.000	-	5024000 [+]	2
786000.000		4238000 [-]	هد)
786000.000	-	[]	
786000.000		÷	
0.185	-	4238000 =	
0. 185	-	×	
18. 500	-	100 =	

3. INVOICE CALCULATION

Ex. Calculate the sub-totals and grand total of the invoice value.

Item	Quantity	Unit price	Total
A	29	28. 30	820.70
В	105	290.00	30, 450. 00
C	63	523.00	32, 449.00
D	47	67. 30	3, 163. 10
		Grand total	67, 382. 80




4. DEPRECIATION CALCULATION

Ex.	Obtain the price of fixed assets as booked at the end of each period (cost: \$500,000, Life: 5 years, depreciation rate: 0.369)
	(COST: \$500,000, Lite . 5 years, depreciation rate . 5.55)

1st year	$500,000 - (500,000 \times 0.369) = A$
2nd year	$A - (A \times 0.369) = B$
3rd year	$B - (B \times 0.369) = C$
4th year	$C - (C \times 0.369) = D$
5th year	$D - (D \times 0.369) \approx E$

(Quantities in parenthesis are the depreciation of a corresponding year)



5. PROPORTIONAL DIVISION


Ex.

portion to their	among stores in pr	he profits (\$ 78,000)	Divide t
		\$45,000	A Store
		\$34,000	B Store
		\$23,000	C Store
0		6T CA	
0		3G CM	
45000.000	→ [45000 +	
79000.000	→ [34000 [+]	
102000.000	→ [23000 [+]	
102000.000	[
102000.000		M.+	
78000.	[78000 ÷	
102000, 000		RM	
0.764	[
0.764	-	×	
34380.000	-	45000 =	
25976. 000 E	- [34000 =	
17572.000		23000 =	

6. PROBABILITY CALCULATION

Ex. Obtain the probability that the "10", "Jack", "Queen", "King", and "Ace" of Hearts can be collected the first try in a bridge game.


$$P = \frac{5}{52} \times \frac{4}{51} \times \frac{3}{5} \times \frac{2}{49} \times \frac{1}{48}$$



That is, the chance comes once in 2,598,960 times.

7. CREDIT LOAN PAYMENT CALCULATION

Ex. Obtain each of 10 monthly installments for a \$ 318,000 loan borrowed at the interest rate of 2.3% per month.




=}	-	0. 2031
CM	-	0. 2031
M-	-	0. 2031
● 023 ÷		0.023
RM		0. 2031
		0.1132
×	-	0.1132
318000 =		35997. 6000

8. SIMPLE INTEREST/COMPOUND INTEREST CALCULATION

- Ex. \$ 10,000 is invested at 5.5% per annum.

 Total assets after five years are to be calculated with simple interest and compound interest.
- (a) Simple interest


 Total assets = (Original investment) x (1 + annual interest x years)



(b) Compound interest

Total assets = (Original investment) x (1 + annual interest) years

= 10,000 (1 + 0.055)⁵



9. HIGH-POWER MULTINOMINAL CALCULATION

Ex.	y= 3 x ⁴ + 6 x ³ -	$8 x^2 + x - 1$			
Calculat	e y when $x = 8$.				
	6 ₇ Σ (■	EA			0
	3	EM		+ [0
	2	8 ×		· [8.
		×	_	- [64.
		×	_	→ [512.
		$[\times]$	-	-	4096.
		3 =	-	· [12288.
		8 ×	-	+	8.
		×	, -	→	64.
		×	.2	→	512.
		6 =	-	-	3072.
		8 ×	-	+	8.
		×	-	→ <u> </u>	64.
		[-] 8 [=]		-	-512.
		8 🙀	-	+	8.
		1 1		→	1.

RM

8. BATTERY RECHARGING

- * Recharge before using for the first time.
- * Built-in lifetime rechargeable CADNICA batteries. The Cadnica batteries are rechargeable, small, hermetically sealed cells. They never need replacing and are handy and ecomomical in usc.
- Recharging procedure
 - 1. Insert adaptor AC plug into power socket.
 - 2. Insert adaptor DC plug into three pin socket as far as it will go.
 - 3. Recharging takes place whether the power switch is ON or OFF and recharging is possible even when the calculator is in use.
- Recharging time Recharging of totally exhausted batteries takes at least 15 hours at power switch off.
- * Battery alarm lamp

Lamp	Battery condition
Light-off	Recharging unnecessary
Light-on	Recharging absolutely necessary

9. SPECIFICATIONS-

Type

Electronic desk top calculator

Model

ICC-1418D

Numeric key

10-key system

Display

Full size fluorescent tubes, with zeros suppression,

error lamp, minus sign, battery alarm lamp.

Decimal point

Floating input/Fixed output (0, 2, 3, 4, 6) round-off/

drop-off

Memory

Capacity

1 memory

Add/sub.

Max. 14 digits ± 14 digits

Multiplication:

Multiplicand + Multiplier ≤15 digits

Products

Max. 14 digits

Division:

Max. 14 digits Dividend:

Divisor:

Quotient:

Max. 14 digits Max. 14 digits

Functions

4-rules, successive multi. and div., constant multi. and div., mixed calculation, power calculation, products

sum and difference, reciprocal calculation, memory

calculation, applied calculations and others.

Components

Mos-LSIs, Hybrid-ICs

Operating temp.

 $0^{\circ} \sim 40^{\circ} \text{C} \quad (32^{\circ} \text{F} - 104^{\circ} \text{F})$

Power supply

AC Local voltage ±10% 50/60 Hz Adaptor:

DC 6.2 V, 7.8V Calculator:

Adaptor:

AC 8W

Power consumption

Calculator: DC 4.5W

Dimensions

 $60(H) \times 226(W) \times 140(D) \text{ mm}$

 $2-3/8(H) \times 8-15/16(W) \times 5-9/16(D)$ inch

Weight

1.3 kg (2 lbs.14ozs.)



Sanyo Electric, Inc., Office Equipment Division 51 Joseph Street, Moonachie, N.J. 07074

Printed in Japan R-4770297